

Ferrous Cobalt Saw Blades

FERROUS AND STAINLESS STEEL

SCX HSS -E-Cobalt M35 Fully Hardened and Tempered to 64/66Rc. Black Finish (BL-OV) Steam Oxide Vapor Treatment Standard.

Part Number	Diameter		Kerf mm	Bore Size	Pinholes Qty./Dia./B.C.	Hub Diameter
	mm	in.				
CQ400A	160mm	6.30"	1.2mm	32mm	1/8/50 1/9/60	99mm
CQ402A	160mm	6.30"	1.5mm	32mm	1/8/50 1/9/60	99mm
CQ404A	200mm	7.87"	2.0mm	32mm	2/8.5/45 2/12/64	90mm
CQ406A	200mm	7.87"	2.0mm	32mm	2/8.5/45 4/9/50 2/12/64	90mm
CQ408A	225mm	8.86"	1.6mm	32mm	2/8.5/45 4/9/50 2/12/64	90mm
CQ410A	225mm	8.86"	1.6mm	40mm	2/9/55 4/12/64	140mm
CQ412A	225mm	8.86"	2.0mm	32mm	2/8.5/45 4/9/50 2/12/64	90mm
CQ414A	225mm	8.86"	2.0mm	32mm	2/8.5/45 2/12/64	90mm
CQ416A	225mm	8.86"	2.0mm	40mm	2/9/55 4/12/64	140mm
CQ418A	250mm	9.84"	1.6mm	40mm	2/9/55 4/12/64	90mm
CQ420A	250mm	9.84"	1.6mm	32mm	2/8.5/45 2/12/64	90mm
CQ422A	250mm	9.84"	2.0mm	32mm	2/8.5/45 2/12/64	90mm
CQ424A	250mm	9.84"	2.0mm	32mm	2/8.5/45 4/9/50 2/12/64	110mm
CQ426A	250mm	9.84"	2.0mm	40mm	2/9/55 4/12/64	90mm
CQ428A	250mm	9.84"	2.5mm	32mm	2/8.5/45 2/12/64	90mm
CQ430A	250mm	9.84"	2.5mm	32mm	2/8.5/45 4/9/50 2/12/64	110mm
CQ432A	250mm	9.84"	2.5mm	40mm	2/9/55 4/12/64	90mm
CQ434A	275mm	10.83"	2.0mm	32mm	2/8.5/45 2/12/64	100mm
CQ436A	275mm	10.83"	2.0mm	40mm	2/9/55 4/12/64	100mm
CQ438A	275mm	10.83"	2.5mm	32mm	2/8.5/45 2/12/64	100mm
CQ440A	275mm	10.83"	2.5mm	32mm	2/8.5/45 4/9/50 2/12/64	110mm
CQ442A	275mm	10.83"	2.5mm	40mm	2/9/55 4/12/64	100mm
CQ444A	275mm	10.83"	3.0mm	32mm	2/8.5/45 2/12/64	100mm
CQ446A	275mm	10.83"	3.0mm	40mm	2/9/55 4/12/64	100mm
CQ448A	300mm	11.81"	2.5mm	32mm	2/8.5/45 2/12/64	100mm
CQ450A	300mm	11.81"	2.5mm	32mm	2/8.5/45 4/9/50 2/12/64	110mm
CQ452A	300mm	11.81"	2.5mm	38mm	2/9/55	100mm
CQ454A	300mm	11.81"	2.5mm	40mm	2/9/55 4/12/64	100mm
CQ456A	300mm	11.81"	3.0mm	32mm	2/8.5/45 4/9/50 2/12/64	100mm
CQ458A	300mm	11.81"	3.0mm	40mm	2/9/55 4/12/64	100mm
CQ460A	300mm	11.81"	3.5mm	32mm	2/8.5/45 2/12/64	100mm
CQ462A	300mm	11.81"	3.5mm	40mm	2/9/55 4/12/64	100mm

A = Available Item Shipped within 8 working days from the time the order is placed.
Bore sizes and mounting holes not listed are available by special quote only.

STANDARD SAW BLADES

DISPOSABLE SAW BLADES

CUSTOM SAW BLADES

COLD SAW BLADES

INDEX

Ferrous Cobalt Saw Blades

FERROUS AND STAINLESS STEEL

SCX HSS -E-Cobalt M35 Fully Hardened and Tempered to 64/66Rc. Black Finish (BL-OV) Steam Oxide Vapor Treatment Standard.

Part Number	Diameter		Kerf mm	Bore Size	Pinholes Qty./Dia./B.C.	Hub Diameter
	mm	in.				
CQ464A	315mm	12.40"	2.5mm	32mm	2/8.5/45 4/9/50 2/12/64	100mm
CQ466A	315mm	12.40"	2.5mm	32mm	2/8.5/45 2/12/64	100mm
CQ468A	315mm	12.40"	2.5mm	40mm	2/9/55 4/12/64	100mm
CQ470A	315mm	12.40"	3.0mm	32mm	2/8.5/45 4/9/50 2/12/64	100mm
CQ472A	315mm	12.40"	3.0mm	32mm	2/8.5/45 2/12/64	100mm
CQ474A	315mm	12.40"	3.0mm	40mm	2/9/55 4/12/64 2/12.5/75 PH	100mm
CQ476A	325mm	12.80"	2.5mm	32mm	2/8.5/45 2/12/64	100mm
CQ478A	325mm	12.80"	2.5mm	40mm	2/9/55 4/12/64	100mm
CQ480A	325mm	12.80"	3.0mm	40mm	2/9/55 4/12/64	100mm
CQ482A	350mm	13.78"	2.5mm	32mm	2/8.5/45 4/9/50 2/12/64	120mm
CQ484A	350mm	13.78"	2.5mm	32mm	2/8.5/45 2/12/64	120mm
CQ486A	350mm	13.78"	2.5mm	40mm	2/9/55 4/12/64	120mm
CQ488A	350mm	13.78"	2.5mm	50mm	4/15/80 4/15/85	120mm
CQ490A	350mm	13.78"	3.0mm	32mm	2/8.5/45 2/12/64	120mm
CQ492A	350mm	13.78"	3.0mm	32mm	2/8.5/45 4/9/50 2/12/64	120mm
CQ494A	350mm	13.78"	3.0mm	40mm	2/9/55 4/12/64	120mm
CQ496A	350mm	13.78"	3.0mm	50mm	2/9/55 4/12/64	120mm
CQ498A	370mm	14.57"	3.0mm	32mm	2/8.5/45 2/12/64	120mm
CQ500A	370mm	14.57"	3.0mm	40mm	2/9/55 4/12/64	120mm
CQ502A	370mm	14.57"	3.0mm	50mm	4/15/80 4/15/85	120mm
CQ504A	400mm	15.75"	3.0mm	40mm	2/9/55 4/12/64	120mm
CQ506A	400mm	15.75"	3.0mm	50mm	4/15/80 4/15/85	120mm
CQ508A	400mm	15.75"	3.5mm	40mm	2/9/55 4/12/64	120mm
CQ510A	400mm	15.75"	3.5mm	50mm	4/15/80 4/15/85	120mm
CQ512A	425mm	16.73"	3.5mm	40mm	2/9/55 4/12/64	120mm
CQ514A	425mm	16.73"	3.5mm	50mm	4/15/80 4/15/85	120mm
CQ516A	450mm	17.72"	3.5mm	40mm	2/9/55 4/12/64	130mm
CQ518A	450mm	17.72"	4.0mm	40mm	2/9/55 4/12/64	130mm
CQ520A	450mm	17.72"	3.5mm	50mm	4/15/80 4/15/85	130mm

A = Available Item Shipped within 8 working days from the time the order is placed.
Bore sizes and mounting holes not listed are available by special quote only.