

# FunctionLINE – Soft Touch Aggregates



## FunctionLINE Soft Touch Aggregate

The Soft-Touch aggregate head accurately follows the contours of your stock, automatically compensating for up to 10mm of variance to maintain constant depth-of-cut. Floating pressure is adjustable from 1/4 lb. to 20 lbs. Compressed air provides saw dust evacuation.

### Features:

- Up to 10mm of compensation for surface variation
- Eliminate re-work processing
- Optional chip guide directs dust into the machine's dust hood for a cleaner work environment

### Includes:

- Collet nut and wrench, standard floating bell, ER25 or ER32 output (your choice)



Boring



Milling



Sanding/  
Finishing

<b>Max Speed Input (Spindle)</b>	18,000 R.P.M. (24,000 R.P.M option)
<b>Floating Pressure</b>	Adjustable from 1/4 lb. to 20 lbs.
<b>Floating Range</b>	10 mm (with 10mm adjustment)
<b>Floating Bell</b>	70mm deep x 105 mm I.D.
<b>Max Torque</b>	10 ft/lbs
<b>Gear Ratio</b>	1:1
<b>Lubrication</b>	Grease
<b>Max Temp.</b>	85° C / 185° F
<b>Output Direction</b>	Same as machine spindle
<b>Tool Interfaces</b>	Modular

